

### Dared HPA-55L Portable Headphone Amplifier



#### Specifications:

- . Max. Power Output  
2x300mW (Single-end Output Loading: 16 $\Omega$ )  
2x1000mW (Balanced Output Loading: 16 $\Omega$ )
- . Frequency Response: 10Hz-30kHz
- . S/N Ratio: 98dB
- . Max. Power Consumption: 3500mW
- . Working Hours of Batteries (Fully Charged): Over 12 Hours
- . Input Port: 3.5mm phono jack
- . Headphone Output Port: 3.5mm Single-end Phono Jack output x1,  
3.5mm Balanced Phono Jack output x1
- . Input Impedance: 47k $\Omega$
- . Output Internal Resistance: 5 $\Omega$  (Single-end), 10 $\Omega$  (Balanced)
- . Damping Factor: 7
- . Q Factor: 0.75
- . Max. Signal Input Level: 3V (RMS)
- . DV Charging Power Supply: DC 12V 500ma
- . Batteries Rechargeable Life Time: over 500 times
- . Dimensions: 122x65x21mm (HxWxD)
- . Weight: 126g

#### WorldWide Sales & Marketing Office

Luen Hing Electrical (HK) Limited

Address: G/F., 152 Apliu Street, Shamshuipo, Kowloon, Hong Kong

Tel: +852 2728 8745 Fax: +852 2729 2962

Email: [worldsales@dared.com.hk](mailto:worldsales@dared.com.hk)

[www.dared.com.hk](http://www.dared.com.hk)